

QwA1

[illegible]

wherein said system reset signal output from said system reset output section is supplied to both chips of said central processing section and said peripheral control section.

3. A reset control system according to claim 1, wherein said system reset output section is provided in the chip of said peripheral control section.

5. A reset control system according to claim 1, further comprising a mask processing section for masking said external reset signal when said emulator

*Dubai* is in operation.

6. A reset control system according to claim 1, further comprising a synchronization processing section for synchronizing activation timings after reset between said central processing section and said peripheral control section, said synchronization processing section being formed on at least one of the chips of said central processing section and said peripheral control section.

7. A reset control system according to claim 6, wherein said synchronization processing section comprises an activation enable signal output section for outputting an activation enable signal for instructing to enable activation after elapse of a predetermined time after reset of said central processing section or said peripheral control section.

8. A reset control system according to claim 5, further comprising a synchronization processing section for synchronizing activation timings after reset between said central processing section and said peripheral control section, said synchronization processing section being formed on at least one of the chips of said central processing section and said peripheral control section.

9. A reset control system according to claim 8, wherein said synchronization processing section comprises an activation enable signal output section for outputting an activation enable signal for

200A1  
instructing to enable activation after elapse of a predetermined time after reset of said central processing section or said peripheral control section.

10. A reset control system for a system having a central processing section and a peripheral control section which are formed on separate chips, said reset control system comprising:

a reset selection section for selectively outputting, as a system reset signal, one of an external reset signal and an emulator reset signal based on a reset instruction from an emulator for independently implementing a function of said central processing section,

wherein said system reset signal output from said reset selection section is supplied to both chips of said central processing section and said peripheral control section.

11. A reset control system according to claim 10, further comprising a synchronization processing section for synchronizing activation timings after reset between said central processing section and said peripheral control section, said synchronization processing section being formed on at least one of the chips of said central processing section and said peripheral control section.

12. A reset control system according to claim 11, wherein said synchronization processing section comprises an activation enable signal output section

Sub A1  
for outputting an activation enable signal for  
instructing to enable activation after elapse of a  
predetermined time after reset of said central  
processing section or said peripheral control section.

13. A reset control system for a system having a  
central processing section, said reset control system  
comprising a mask processing section for masking an  
external reset signal when an emulator for  
independently implementing a function of said central  
processing section is in operation.

Sub A1  
14. A reset control method for a system having a  
central processing section and a peripheral control  
section which are formed on separate chips, said  
method comprising the steps of:

masking an external reset signal when an emulator  
for independently implementing a function of said  
central processing section is in operation;

generating a system reset signal on the basis of  
the masked external reset signal and an emulator  
reset signal based on a reset instruction from said  
emulator; and;

supplying said system reset signal to both chips  
of said central processing section and said  
peripheral control section.

15. A method according to claim 14, wherein said  
system reset signal is generated by OR-operating said  
emulator reset signal and said masked external reset  
signal.

